

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18
19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36
37	38	39	40	41	42	43	44	45	46	47	48	49	50	51	52	53	54

FREE LOTTO  
\$1,000,000.00  
Click 2 Win  
TONIGHT

CLICK 6  
NUMBERS  
OR  
Quick Pick

IBM.

Intellectual Property Network

Patent &amp; Research

IPN Home | Search | Order | Shopping Cart | Login | Site Map | Help

Patent Plaques



# JP8155303A: EXHAUST GAS PURIFICATION CATALYST CARRIER, PRODUCTION OF THE SAME AND EXHAUST GAS PURIFICATION CATALYST USING THE SAME AND METHOD FOR PURIFYING EXHAUST GAS

[View Images \(1 pages\)](#)

Country: JP Japan

Inventor(s): SUZUKI KENICHIRO  
TSUJI RYUSUKE  
HAYAKAWA YOSHIO  
DOI HARUO  
SUGIURA MASAHIRO

## BEST AVAILABLE COPY

Applicant(s): TOYOTA CENTRAL RES & DEV LAB INC



[News, Profiles, Stocks and More about this company](#)

Issued/Filed Dates: June 18, 1996 / Dec. 1, 1994

Application Number: JP1994000298169

IPC Class: B01J 023/648; B01D 053/86; B01D 053/94; B01J 023/20; B01J 023/64; B01J 023/74; B01J 023/847; B01J 023/89; B01J 032/00; B01J 035/10;

Abstract: **Purpose:** To more efficiently remove NOx and HC(hydrocarbon) in an exhaust gas.

**Constitution:** This catalyst carrier consists of an interlayer-crosslinked niobium based layer perovskite. In the layer perovskite, the layers consisting of layer anion groups are crosslinked together by silicon dioxide, whose group is represented by the general formula,  $Mn-1Nb_nO_{3n+1}$  (wherein: M is at least one metal selected from alkaline earth metals of Ca, Sr and Ba, rare earth elements of Y, La, Ce and Nd and transition metals of Mo, Fe, Co and Ni; (n) is a number of =2). Also, the pore size in diameter and specific surface area of the perovskite are adjusted to 10 to 40 $\mu$ m; and 250 to 500m<sup>2</sup>/g respectively. Since the layers are crosslinked together by columnar silicon dioxide, a large number of uniform pores are formed in the space between every adjacent two of the